## AL02-04-100 : Semi Automatic Vertical Autoclave

Suitable for the sterilization of:

- Liquids such as nutrient media and buffer solutions
- Solid items such as pipettes, tubes and filters
- Glassware and plastic articles
- Waste sterilization



## Features:

- Heat-resistant plastic covering on lid Prevents contact with hot parts and protects from burning.
- **Pressure-dependent door lock** Prevents the door from being opened when under pressure.
- **Door lock safety switch** Prevents the sterilization program from being started if the door has not been closed properly.
- Excess temperature safety device Switches off the heating elements if too high a temperature is attained.
- Overpressure valve Releases over pressure in order to prevent high pressure risk.

## **Technical Specification:**

Chamber Volume (liter): 23

Chamber Size (øxDepth in mm): 250x400 Voltage(nominal +/-10%) 50/60Hz (V): 220-240 Heating Capacity (Kw): 2.2

Ambient Temperature ( $\mathfrak{C}$ ): 5 to 40 degrees Semi Automatic Dimensions\* WidthxHeightxDepth (mm): 500x665x335

Shipping Weight: 57 kg

**Loading Capacity:** 

Erlenmeyer	Nr. of bottles	Schott-Duran	Nr. of Bottles
250 mL	2 x 5	250 mL	2 x 8
500 mL	2 x 4	500 mL	2 x 5
1000 mL	1	1000 mL	4
2000 mL	1	2000 mL	1
3000 mL	1	5000 mL	1
5000 mL	1	10000 mL	-

<sup>\*</sup>Dimensions refer to unit housing including levelling feet. Technical data are subject to change without prior notice.