Dri-Block® Heaters

Three block inserts

DB-3D and DB-3DL



- Can hold up to 3 aluminium insert blocks or one 96-well plate block
- Bright orange LED digital display for fast and accurate setting of temperature
- DB-3DL temperature range from ambient to 100°C and DB-3D up to 200°C
- Powerful heater for fast heat-up rate: 30°C to 200°C in just 25 minutes
- Interchangeable insert blocks to accommodate a variety of tubes
- Temperature stability at 40°C: ± 0.1°C

Technical Specification

| | | DB-3D | DB-3DL |
|---------------------------------|--------------------|------------------|------------------|
| Temperature range | | Ambient to 200°C | Ambient to 100°C |
| Temperature stability @ 40°C | | ±0.1°C | ±0.1°C |
| | @ 100°C | ±0.15°C | ±0.15°C |
| Temperature setting | | Push Button | Push Button |
| Temperature display | | Orange LED | Orange LED |
| Temperature scale graduation | | No graduation | No graduation |
| Maximum tem | perature variation | | |
| between identical blocks @ 40°C | | 0.2°C | 0.2°C |
| Set point accuracy | | ±1°C | ±1°C |
| Maximum number of blocks | | 3 | 3 |
| Heat up time | 30-37°C | 11 minutes | 8 minutes |
| | 30-56°C | 15 minutes | 9 minutes |
| | 30-Max. | 25 minutes | 12 minutes |
| RS232 option available | | Yes | No |
| Heater power | | 450W | 450W |
| Dimensions (L x W x H), mm | | 279 x 260 x 105 | 279 x 260 x 105 |
| Voltage | | 230V, 50-60Hz | 230V, 50-60Hz |
| Shipping Weight, kg | | 6 | 6 |

Ordering Information

| | Product codes | Product codes | |
|-------------------------|---------------|---------------|--|
| Description | 230V | 115V | |
| DB-3DL ambient to 100°C | FDB03LDD | FDB03LDP | |
| DB-3D ambient to 200°C | FDB03DD | FDB03AP | |

Techne Catalogue Page 33