

Pass-through sterilizers

Application

- drying of painted and lacquered components
- drying/sterilizing of components between clean and dirty zones
- drying of components on production line

Standard and optional accessories are the same like for the SR range. Other capacities on request.



SRWP 115

SRWP 240



Parameter		SRWP 115	SRWP 240
air convection		forced	
chamber capacity ¹ [l]		105	240
door type		solid /door with viewing window (option)	
temperature range [°C]		5°C above ambient temperature ...+250°C	
temperature resolution [°C]		every 0,1	
controller		microprocessor with external LCD graphic display	
interior		acid-proof stainless steel to DIN 1.4301	
housing	-	powder coated sheet	
	INOX/G	stainless steel linen finish	
overall dims ² [mm]	width	700	840
	height	910	1180
	depth	700	770
internal dims [mm]	width	460	600
	height	530	800
	depth	430	500
max shelf workload ⁵ [kg]	-	10	10
	PW ³ version	50	100
max unit workload [kg]	-	60	90
	W ⁴ version	120	300
nominal power [W]		2500	3100
weight ⁶ [kg]		65	126
over temperature protection		class 2.0 to DIN 12880 / class 3.1 (option)	
power supply*		230 V 50 Hz	
shelves fitted/max		2/7	3/10
warranty		24 months	
manufacturer		POL-EKO-APARATURA	

all the above technical data refer to standard units (without optional accessories)

* also available: 230V 60Hz, 115V 60Hz, 3P 230V 60Hz (according to model)

1 - working capacity of chamber can be smaller

2 - depth doesn't include 50 mm of power cable

3 - reinforced shelf

4 - reinforced version

5 - on uniformly loaded surface

6 - for units with solid door without optional equipment