



# Portable Mini CO<sub>2</sub> Incubator

## Compact & Economical Mini CO<sub>2</sub> Incubator



- 16Liter Chamber
- 6.8 kg Light Weight to carry
- Portable Use with carrying handle(Car Plug available)
- Economical Price & Compact Design for Personal Use
- Available size to use in work station or Clean bench
- Digital Temperature & CO<sub>2</sub> Set-Up
- Forced Air Circulation
- Excellent Temperature Uniformity
- Cooling with very low noise
- Cooling & Heating by peltier

- Accessories  
Stainless steel Water Tray  
Power Plug & Car Jack  
Stainless steel Shelf(Optional)



Car Jack



## Portable Mini CO<sub>2</sub> Incubator

### Specifications

Items	Specification
Chamber Volume	16Liters
Temperature Range	15℃ ~ 45℃ at Ambient 25℃
Temperature Accuracy	±0.25℃
Temperature Control	Micom
CO <sub>2</sub> Range	0 ~ 20%
CO <sub>2</sub> Sensor	Dual Beam IR Sensor
CO <sub>2</sub> Accuracy	±0.1%
Gas Pressure	0.7Bar (Max.1Bar)
Display	LED Display
Cooling & Heating	By Peltier
Shelf	1(Polycarbonate, Standard)~3(Max)
In & Outside Material	ABS resin
Inside Dimension	224(W) x 200(D) x 340(H)mm
Outside Dimension	292(W) x 333(D) x 433(H)mm
Weight	6.8kg
Power / Freequency	DC 12V, AC110V or 220V , 50/60Hz
Power Consumption	DC-COLD : 46W , HOT : 48W AC-COLD : 63W, HOT : 63W
Options	
203M-SHELFSUS	Stainless steel Shelf
203M-Hole	Access Port



**N-BIOTEK**  
Leading Life Science

CO<sub>2</sub> INCUBATORS  
IR CONCENTRATORS  
LIVE CELL STATIONS  
SHAKERS & WATER BATHS  
WORK STATIONS  
OTHERS  
BIO MEDICAL EQUIPMENT  
BIO CLEAN ROOM

402-803 Techno-Park Yakdae-dong,  
Wonmi-gu, Bucheon-si, Gyeonggi-do,  
420-734, KOREA  
TEL: 82-32-321-2100  
FAX: 82-32-328-2372  
**E-mail: export@n-biotek.com**  
Web: www.n-biotek.com