

# Size reduction with Rotor Mills



**Retsch**<sup>®</sup>  
Solutions in Milling & Sieving

# Ultra Centrifugal Mill ZM 200

The powerful drive of the innovative Ultra Centrifugal Mill ZM 200 ensures rapid grinding results. Together with its extremely efficient operation the ZM 200 can prepare 100 samples or more per day for analysis.

**More on page 4.**





**Milling**

- Jaw Crushers
- **Rotor Mills**
- Cutting Mills
- Knife Mills and Blenders
- Disc Mills
- Mortar Grinders
- Mixer Mills
- Planetary Ball Mills

**Sieving**

**Assisting**

**Ultra Centrifugal Mills**

- Applications 4
- Ultra Centrifugal Mill ZM 200 5
- Rotors and ring sieves 6
- Accessories 7
- Technical data 7
- Order data 8



**Rotor Beater Mills**

- Applications 9
- Rotor Beater Mill SR 200 10
- Rotor Beater Mill SR 300 10
- Retaining frames and sieves 11
- Accessories 11
- Technical data 11
- Order data 12



**Cross Beater Mills**

- Applications 13
- Cross Beater Mill SK 100 14
- Bottom sieves 15
- Accessories 15
- Technical data 15
- Order data 16



The **rotor mill series** includes ultra centrifugal mills, rotor beater mills and cross beater mills. Depending on the particular instrument **they are suitable for the preliminary and fine size reduction of soft, fibrous and also hard materials**. A final fineness of down to 40 µm can often be achieved in the first working step. The maximum feed size depends on the mill and ranges from 10 to 15 mm. Material which is larger than this must first undergo preliminary size reduction.

**Preliminary size reduction**



**For the coarse and preliminary size reduction** of hard, brittle or hard-tough materials the **RETSCH jaw crushers** have proven themselves in practice. In contrast, **bulky, soft, fibrous or tough materials are best processed in RETSCH cutting mills**.

**Sample dividers**



Sample dividers, rotary tube sample dividers, sample splitters – with **RETSCH sample dividers** you will obtain **representative part samples** from pourable powders and bulk goods **for meaningful analysis results**.

The main areas of application for ultra centrifugal mills are:

**Agriculture**

Fertilizers, plant materials, seeds, straw, tobacco, wood

**Biology**

Animal tissue, bones, collagen, dried larvae

**Chemicals and plastics**

Activated charcoal, plastics (PET, PP, ABS, polystyrene, polycarbonate etc.), powder coatings, rubber granulate, super-absorbent polymers, synthetic resins

**Environmental research**

Electronic components (circuit boards), fossil and secondary fuels, waste

**Food and feeds**

Coffee beans, corn, feed pellets, dried fruit and vegetables, rice, spices, sweets, tea leaves

**Geology and metallurgy**

Bentonite, coal, coke, limestone

**Medicine and pharmaceuticals**

Pharmaceutical raw materials and finished products

and many more...

# Applications Ultra Centrifugal Mill

The powerful and versatile ZM 200 offers **the ultimate in performance and operating comfort**. The mill pulverizes a great variety of soft to medium-hard and fibrous substances extremely fast, thus allowing for a high sample throughput. The ultra centrifugal mill is used in both quality control and R&D. Thanks to its high efficiency and superior results the Ultra Centrifugal Mill ZM 200 has established itself as a **standard laboratory device** in the feeds industry as well as for chemical and agricultural applications. It is frequently used for **sample preparation to NIR and ICP analyses**.

## Free test grinding

As part of RETSCH's professional customer support we offer our customers the individual advice required to find the optimum solution for their sample preparation task. To achieve this our application laboratories process and measure samples free-of-charge and provide a recommendation for the most suitable method and instrument.

For more information please visit our website [www.retsch.com/testgrinding](http://www.retsch.com/testgrinding).



## Application examples

Ultra Centrifugal Mill	Accessories/ grinding aids	Rotor	Ring sieve aperture size	Feed size	Sample amount	Grinding time	Speed	Final fineness
<b>Bentonite</b>	Cyclone, Vibratory Feeder	12 teeth	0.25 mm	0-5 mm	1,500 g	15 min.	18,000 rpm	90% <63 µm
<b>Coal</b>	Cyclone, Vibratory Feeder	12 teeth	0.2 mm	1-15 mm	550 g	5 min.	18,000 rpm	99% <100 µm
<b>Corn</b>	Cyclone	12 teeth	1 mm	5 mm	100 g	15 s	18,000 rpm	90% <500 µm
<b>Feed pellets</b>		12 teeth	2 mm	10x30 mm	200 g	2 min.	18,000 rpm	80% <500 µm
<b>Fertilizer</b>		12 teeth	0.25 mm	1-4 mm	80 g	2 min.	18,000 rpm	<100 µm
<b>Licorice (a) / Wine gum (b)</b>	Dry ice, talc	12 teeth	2 mm* (a) / 0.5 mm* (b)	1-15 mm	15 g	3 min.	18,000 rpm	homogeneous <300 µm
<b>Powder coating</b>	Cyclone, Vibratory Feeder	12 teeth	0.08 mm*	1-15 mm	120 g	2 min.	18,000 rpm	80% <53 µm
<b>PP granules</b>	Pre-cooling with LN <sub>2</sub>	12 teeth	0.75 mm	1-3 mm	40 g	7 min.	18,000 rpm	90% <500 µm
<b>Rice</b>	Cyclone, Vibratory Feeder	12 teeth	0.5 mm	2-8 mm	400 g	2.5 min	18,000 rpm	80% <200 µm
<b>Saffron fibres</b>		6 teeth	0.5 mm	1-15 mm	5-10 g	10 s	18,000 rpm	<200 µm
<b>Secondary fuels</b>	Cyclone, dry ice	12 teeth	1 mm	1-10 mm	200 g	5 min.	18,000 rpm	80% <500 µm
<b>Tablets</b>		24 teeth	0.08 mm	10-20 mm	25 g (20 tablets)	30 s	18,000 rpm	80% <40 µm

\*Distance sieve  
This chart serves only for orientation purposes.

RETSCHE's application database contains more than 1,000 application reports. Please visit [www.retsch.com/applicationdatabase](http://www.retsch.com/applicationdatabase).

# Ultra Centrifugal Mill

## ZM 200

Versatile and efficient

### Benefits at a glance

- Powerdrive with optimally matched frequency converter and 3-phase motor
- Wide speed range, adjustable from 6,000 to 18,000 rpm
- Patented cassette system for maximum sample recovery and easy cleaning
- Defined final fineness
- Comfortable safety housing with automatic cover closure
- Motor compartment and electronics protected against dust and material penetration
- Comfortable parameter setting via display and ergonomic 1-button operation
- Wide range of accessories



ZM 200

### High-speed power for excellent grinding results

With the Ultra Centrifugal Mill ZM 200 RETSCH offers a mill with previously unmatched performance. The heart of the ZM 200 is the **innovative Powerdrive** which ensures higher performance with increased torque. The perfectly matched frequency converter and 3-phase motor provide a considerably higher throughput when compared with other rotor mills. Temporary overloads are easily balanced at continued output which ensures particularly effective grinding.

The extremely quick size reduction process increases sample throughput

while the **2-step rotor-ring sieve system** ensures that the sample characteristics remain unaltered.


Soft, elastic products such as plastics, which do not process well at room temperature, can be fed into the mill after **embrittlement with liquid nitrogen or dry ice**.

Because of the efficient size reduction technique and the comprehensive range of accessories **the ZM 200 ensures the gentle preparation of analytical samples in a very short time.**

### ZM 200 technology

In the ultra centrifugal mill size reduction takes place by impact and shearing effects between the rotor and the fixed ring sieve. The feed material passes through the hopper (with splash-back protection) onto the rotor. Centrifugal acceleration throws it outward with great energy and it is pre-crushed on impact with the wedge-shaped rotor teeth moving at a high speed. The particles are then finely ground between the

rotor and the ring sieve. This 2-step grinding ensures particularly gentle but fast processing. The feed material only remains in the grinding chamber for a very short time, which avoids the risk of overheating and ensures that the characteristics of the sample to be analyzed remain unaltered. The ground sample is collected in the cassette surrounding the grinding chamber or in the downstream cyclone or paper filter bag.



# ZM 200 – powerful, safe, flexible

## Rotors and ring sieves

The selection of the push-fit rotors and ring sieves depends on the properties of the sample, the required final fineness and the subsequent analysis.

The ring sieve aperture size is primarily chosen according to the required final fineness and the feed material. With most materials approx. **80% of the total sample achieves a fineness of less than half the aperture size of the ring sieve used.**

Rotors and ring sieves are available in various materials and types. The **reinforced rims** provide the ring sieves with greater stability.

Temperature-sensitive, brittle materials such as powder coatings and resins are particularly easy to grind with the **distance sieves** that have been specially developed for this purpose.



(1) Standard ring sieve  
(2) Ring sieve with reinforced rim  
(3) Distance sieve

Rotors and ring sieves with an **abrasion-resistant coating** are used for reducing the size of abrasive substances such as fertilizers.

For **heavy-metal-free size reduction** of non-abrasive materials we recommend the use of rotors and ring sieves made from titanium

together with cassette and covers with a titanium-niobium coating.

**Thanks to the wide range of accessories with rotors, ring sieves and different types of collection systems, the ZM 200 can be easily adapted to suit a wide variety of applications.**

### Rotor selection guide

Rotor	Field of application
6-tooth rotor	coarse, bulky, fibrous goods such as feed pellets, hay and straw
12-tooth rotor	medium-coarse goods such as wheat, oats, corn, tablets, powder coatings and plastics
24-tooth rotor	fine goods such as chemicals, coal and sugar
8-tooth mini-rotor	specially for size reduction of small sample amounts up to 20 ml

## New technology with maximum operating comfort

The ZM 200 is very simple and safe to use. The parameters are easily set via a graphics display and 1-button operation. All relevant data can be comfortably entered or called up, e.g.

- speed
- drive load
- operating hours
- service intervals
- clear text error messages

With manual feeding of the sample, the performance display allows to monitor the load of the drive and to adjust the feed rate for optimized results.

The electronic safety and diagnosis system **virtually rules out operating errors.**



### Suitable for almost any task

Its wide range of accessories and the possibility to individually select the rotor speed make the ZM 200 easily adaptable to any size reduction task.

The feed material is introduced either manually or via an optional load-controlled Vibratory Feeder DR 100 which is connected to the mill through an interface. **The automatic, regular sample feed maximizes the throughput without any risk of overloads and ensures uniform grinding results.** The ground sample is collected in the cassette. The innovative cassette principle ensures easy and loss-free material removal and avoids cross-contamination.

For **grinding larger amounts** we recommend the use of a paper filter bag or a cyclone with a 3 l or 5 l collecting receptacle. The advantages are additional cooling of the sample by the air stream and a more rapid discharge from the grinding chamber via the passage receptacle.

All parts coming into contact with the sample can be removed, cleaned and reassembled without using any tools.



Controlled and uniform material feed:  
ZM 200 with Vibratory Feeder DR 100



Automatic size reduction of large amounts:  
ZM 200 with Vibratory Feeder DR 100 and cyclone

Performance data		ZM 200
Application	fine grinding	
Field of application	agriculture, biology, chemistry/plastics, construction materials, engineering/electronics, environment, food, geology/metallurgy, medicine/pharmaceuticals	
Feed material	soft, medium-hard, brittle, fibrous	
Feed size	<10 mm	
Final fineness*	<40 µm	
Sample volume (nominal)	with standard cassette	up to 300 ml (900 ml)
	with mini-cassette	up to 20 ml (50 ml)
	with paper filter bag	up to 1,000 ml (3,000 ml)
	with cyclone	up to 2,500 ml (3,000 ml), or up to 4,500 ml (5,000 ml)
Speed range	6,000 - 18,000 rpm, freely selectable	
Rotor peripheral speed	31 - 93 m/s	
*depending on feed material and instrument configuration/settings		
Technical data		
Power consumption	approx. 1,300 W (VA)	
W x H x D	410 x 515 x 365 mm	
Weight, net	approx. 38 kg	
Noise values (noise measurement according to DIN 45635-31-01-KL3)		
Emission value with regard to workplace	L <sub>pAeq</sub> 77.5 dB(A)	
Measuring conditions:		
Sample	burnt lime	
Feed size	<5 mm	
Rotor used	12-tooth rotor	
Ring sieve used	0.5 mm trapezoid holes	

### Accessories for grinding small volumes

In many fields, e.g. in the pharmaceutical industry, the required sample amounts are very small. The **mini-cassette** for the ZM 200 for **sample volumes of up to 20 ml**, which is used in combination with the 8-tooth mini-rotor, is the ideal tool for such applications. The loss-free recovery of smaller amounts of sample is made easier by the reduced cassette diameter. Suitable **ring sieves** are available **with ap-**

**erture sizes from 0.08 to 2.00 mm.** If the grinding tools for small volumes are used in the ZM 200 only a small labyrinth disk is required. The necessary accessories are available as a conversion kit.

All parts coming into contact with the sample, including the cassette and ring sieves, are made from corrosion-resistant steel 1.4404 (316).

### Order data for Ultra Centrifugal Mill ZM 200

Ultra Centrifugal Mill ZM 200			Item No.
ZM 200 with cassette (900 ml) (please order push-fit rotor and ring sieve separately)			
ZM 200	for 200-240 V, 50/60 Hz		20.823.0001
ZM 200	for 110 V, 50/60 Hz		20.823.0002
ZM 200	for 120 V, 50/60 Hz		20.823.0003

Push-fit rotors and ring sieves for normal use													Item No.		
Push-fit rotor										6-tooth	12-tooth	24-tooth			
Push-fit rotor, stainless steel										02.608.0040	02.608.0041	02.608.0042			
Ring sieves			Trapezoid holes							Round holes					
Aperture sizes in mm			0.08	0.12	0.20	0.25	0.50	0.75	1.00	1.50	2.00	3.00	4.00	5.00	6.00
Ring sieves, stainless steel															
Item No.: 03.647...			0231	0232	0233	0234	0235	0236	0237	0238	0239	0240	0241	0242	0243
Ring sieves, stainless steel, with reinforced rim, recommended for tough materials															
Item No.: 03.647...			0244	0245	0246	0247	0248	0249	0250	0251	0252	0272	0273	0274	0275
Distance sieves, stainless steel, recommended for temperature-sensitive materials															
Item No.: 03.647...			0253	0254	0255	0256	0257	0258	0259	0260	0304	-	0261	-	-
Distance sieves, stainless steel, square holes, 10 mm, for pre-grinding													03.647.0298		

Push-fit rotors and ring sieves for abrasive products													Item No.		
Push-fit rotor										6-tooth	12-tooth	24-tooth			
Push-fit rotor, stainless steel, with wear-resistant coating										02.608.0043	02.608.0044	02.608.0045			
Ring sieves			Trapezoid holes							Round holes					
Aperture sizes in mm			0.08	0.12	0.20	0.25	0.50	0.75	1.00	1.50	2.00	3.00	4.00	5.00	6.00
Ring sieves, stainless steel, with reinforced rim, wear-resistant coating															
Item No.: 03.647...			-	-	0262	0263	0264	0265	0266	0267	0268	0269	-	-	-

Push-fit rotors and ring sieves for heavy-metal-free grinding													Item No.		
Push-fit rotor										12-tooth					
Push-fit rotor, titanium										02.608.0047					
Cassette, titanium-niobium coating, complete (base, cover and seal)										22.355.0006					
Ring sieves			Trapezoid holes							Round holes					
Aperture sizes in mm			0.08	0.12	0.20	0.25	0.50	0.75	1.00	1.50	2.00	3.00	4.00	5.00	6.00
Ring sieves, titanium, with reinforced rim															
Item No.: 03.647...			0270	0271	0276	0277	0278	0279	0280	0281	0282	-	0283	-	-

Accessories for grinding small volumes													Item No.		
Conversion set for grinding small volumes, consisting of 8-tooth push-fit rotor, labyrinth disc and cassette (50 ml)										22.786.0002					
8-tooth push-fit rotor, corrosion-resistant steel 1.4404 (316)										02.608.0057					
Labyrinth disc										02.706.0247					
Cassette (50 ml), corrosion-resistant steel 1.4404 (316), complete (base, cover and seal)										02.010.0039					
Ring sieves			Trapezoid holes							Round holes					
Aperture sizes in mm			0.08	0.12	0.20	0.25	0.50	0.75	1.00	1.50	2.00	3.00	4.00	5.00	6.00
Ring sieves, corrosion-resistant steel 1.4404 (316)															
Item No.: 03.647...			0287	0288	0289	0290	0285	0291	0292	0293	0294	-	-	-	-

Accessories for grinding large volumes													Item No.
Cyclone for ZM 200 with passage receptacle and holder, with 5 liter collector										22.935.0009			
Cyclone for ZM 200 with passage receptacle and holder, with 3 liter collector										22.935.0010			
Paper filter bags (12 pieces) with passage receptacle and flange										22.261.0003			

Accessories for automatic material feed													Item No.
Feeder kit DR 100, complete with feed attachment and 40 mm push-fit feed chute, length 250 mm, hopper, stand and data cable													
DR 100			for 220-240 V, 50 Hz							22.936.0001			
DR 100			for 110-120 V, 60 Hz							22.936.0002			

Other accessories / Spare parts													Item No.	
Spare cassette (900 ml), stainless steel, complete (base, cover and seal)										02.010.0037				
Spare cassette cover, stainless steel, with seal										22.355.0003				
See price list for further accessories.														

# Applications Rotor Beater Mills

The rotor beater mills are used to grind soft and medium-hard sample materials by impact and shearing. Due to their **robust design** and ability to process large amounts of sample they are ideal for small-scale production and suitable for **installation into automated preparation systems**.

## Free test grinding

As part of RETSCH's professional customer support we offer our customers the individual advice required to find the optimum solution for their sample preparation task. To achieve this our application laboratories process and measure samples free-of-charge and provide a recommendation for the most suitable method and instrument.

For more information please visit our website [www.retsch.com/testgrinding](http://www.retsch.com/testgrinding).



The main areas of application for rotor beater mills are:

### Agriculture

Fertilizer, plant materials, seeds, soils

### Chemicals and plastics

Plastics, powder coatings, resins

### Construction materials

Gypsum

### Food

Feed pellets, herbs, rice, spices, sugar

### Geology and metallurgy

Bentonite, coal, coke, graphite

and many more...

## Application examples

Rotor Beater Mills	Model	Rotor	Retaining frame	Sieve aperture size	Feed size	Sample amount	Grinding time	Final fineness
Animal feed	SR 300*	Standard rotor	360°	1.5 mm	10-12 mm	1,500 g	2.5 min.	95% <1.5 mm
Bentonite	SR 300	Standard rotor	360°	0.12 mm	1-5 mm	500 g	5 min.	95% <100 µm
Biochar	SR 300	Standard rotor	360°	0.25 mm	0-15 mm	4,000 g	10 min.	99% <300 µm
Black Coal	SR 200*	Distance rotor	180°	0.25 mm	1-5 mm	1,800 g	5 min.	98% <200 µm
Coke	SR 300	Standard rotor	360°	0.5 mm	1-10 mm	400 g	2 min.	99% <500 µm
Graphite	SR 300	Distance rotor	180°	0.75 mm	1-10 mm	200 g	15 s	95% <600 µm
Gypsum	SR 200	Distance rotor	180°	1.5 mm	10 mm	3,000 g	3 min.	95% <1 mm
Powder Coating	SR 300*	Distance rotor	360°	0.25 mm	1-10 mm	2,000 g	13 min.	95% <100 µm
Soil	SR 200	Distance rotor	180°	3 mm	0-15 mm	100 g	30 s	98% <2 mm
Spices (goldenrod)	SR 300	Standard rotor	360°	0.5 mm	1-15 mm	100 g	2 min.	90% <0.5 mm
Sugar	SR 300	Distance rotor	360°	0.08 mm	0-1 mm	500 g	5 min.	95 % <30 µm
Wheat	SR 300*	Distance rotor	360°	1 mm	0-5 mm	1,500 g	1 min.	90% <0.75 mm

\*with Vibratory Feeder DR 100  
This chart serves only for orientation purposes.

RETSCH's application database contains more than 1,000 application reports. Please visit [www.retsch.com/applicationdatabase](http://www.retsch.com/applicationdatabase).

# Rotor Beater Mills

## SR 200 and SR 300



SR 300



SR 200

**High sample throughput**

### Size reduction, deagglomeration

RETSCH rotor beater mills are suitable for **coarse and fine size reduction**, either in batches or continuously, as well as for the **deagglomeration** of dry, soft and medium-hard organic and inorganic substances. Typical sample batches start with 0.5 liters. Therefore the mills can be used for sample preparation in the laboratory or in pilot plants for large sample quantities.

### Grinding large volumes in no time

Rotor Beater Mills can process large sample amounts in a very short time due to the large open sieve area of the 360° ring sieves. Their range of applications is just as versatile as the wide range of accessories.

#### Benefits at a glance

- Suitable for batchwise operation of larger quantities
- High final fineness
- Exchangeable grinding and sieve inserts
- Optional grinding inserts 180° for grinding of hard-brittle materials by additional impact
- Optional distance rotor to reduce frictional heat
- Quick-action door lock and motor brake
- Defined final fineness due to bottom sieves with aperture sizes from 0.08 - 10 mm


**The SR 200** with a speed of 2,850 rpm (at 50 Hz) is available in gray cast iron. It has its primary uses for **medium-hard, brittle products** which can be perfectly ground with the standard rotor and the retaining frame that consists of a 180° sieve and a 180° impact insert, **without creating undesired fines**. The preparation of coal samples for calorimetric analyses is a typical application. The mill can be bench-mounted or installed on the optional base frame.

**The SR 300** is the powerful comfort model. Due to the higher rotor speed (8,100 rpm at 50 Hz) and drive performance higher throughputs with a usually larger fine material fraction are obtained. For this reason the SR 300 provides **results comparable to the Ultra Centrifugal Mill ZM 200**, however, it is capable of handling larger batches. Grinding chamber, feed hopper and the material inlet and outlet are **completely made from stainless steel**. The hopper can be screwed off for easy cleaning. The mill is supplied complete with base frame.

### SR 200, SR 300 technology

Size reduction and deagglomeration in rotor mills are achieved by hammering, impact and shear effects. The feed material passes from the hopper into the center of the grinding chamber where it is crushed between the rotor, sieve and grinding insert. As soon as the material is smaller than the aperture size of the sieve, it enters the collecting receptacle.

The quick-acting door lock ensures easy access to the grinding chamber for cleaning. With their motor brake (braking time < 0.5 s), safety switch, splash-back and access barrier in the inlet and outlet areas, rotor beater mills offer the highest degree of operating safety.




# Ideal for laboratory and small-scale production

## Selection of accessories

For soft, fibrous materials we recommend the **retaining frame with ring sieve 360°** (1)+(2). The **retaining frame with grinding insert 180°** (3) with the corresponding sieve (4) combines impact and shear effects and has proven itself with hard, brittle substances, especially on the low-speed SR 200.

The final fineness depends on the aperture size of the sieve, the breaking behavior of the feed material and the rotor speed. With many materials approx. 80% of the ground material is smaller than half the aperture size.

Both rotor mills include the **standard rotor** which provides good results with most products. For thermally sensitive, slightly fatty or oily or particularly soft sample materials, size reduction with the **distance rotor** is ideal. The larger grinding gap ensures a reduction in frictional heat, which prevents the sieve or the rotor from being blocked. This configuration is particularly efficient with the high-speed SR 300.



1. Retaining frame 360° (with ring sieve 360°)
2. Ring sieve 360°
3. Retaining frame with grinding insert 180° (with sieve 180°)
4. Sieve 180°

Performance data	SR 200	SR 300
Applications	size reduction, deagglomeration	
Field of application	agriculture, chemistry/plastics, construction materials, environment, food, medicine/pharmaceuticals	
Feed material	soft to medium-hard	
Feed size*	<15 mm	<15 mm
Final fineness*	<80 µm	<50 µm
Vessel capacity	5 or 30 l	5 or 30 l
Grinding chamber material	gray cast iron	stainless steel

Technical data		
Drive	3-phase and 1-phase motors	
Brake motor	yes	yes
Drive performance	1.1 kW	2.2 kW
Motor speed at 50 Hz (60 Hz)	2,850 rpm (3,420 rpm)	8,100 rpm (9,700 rpm)
Rotor peripheral speed at 50 Hz (60 Hz)	20.5 m/s (24.5 m/s)	58 m/s (69.5 m/s)
W x H x D (with base frame)	560 x 1,150 x 700 mm	560 x 1,200 x 890 mm
Weight (with base frame)	approx. 57 kg	approx. 95 kg

Noise values (noise measurement according to DIN 45635-31-01-KL3)		
Emission value with regard to workplace	L <sub>pAeq</sub> 81 dB(A)	L <sub>pAeq</sub> 91 dB(A)
Measuring conditions:		
Ring sieve	0.5 mm trapezoid	0.5 mm trapezoid
Feed material	rye,	artificial fertilizer
Feed size	up to 15 mm	up to 3 mm

\*depending on feed material and instrument configuration/settings



Rotor Beater Mills are supplied with a collecting receptacle (5 l) made from stainless steel and a textile filter hose. By using the **filter hose** between mill and collector the flow of air produced by the rotating rotor is discharged and back-pressure is avoided. It also **accelerates the material throughput** and ensures a gentle size reduction process. Instead of the textile tube a **ring-type filter with stainless trapezoid hole sheet** (aperture size 63 µm) can be installed to avoid cross contamination and ensure a

higher stability for the collecting receptacle. For additional convenience in cleaning, a dust filter unit is available.

For larger sample amounts we recommend the use of the electromagnetic **Vibratory Feeder DR 100** for uniform material feed and the **30 l collector** with the corresponding filter hose. The use of the vibratory feeder avoids overloads, improves the grinding result and allows for automatic processing of up to 3.5 liters of sample.

Order data for Rotor Beater Mills SR 200, SR 300

Rotor Beater Mills SR 200, SR 300		Item No.
Rotor Beater Mill SR 200, supplied with standard rotor, filter hose (240 mm), collecting receptacle (5 l) (Please order retaining frame, sieves and, if required, base frame separately)		
SR 200	for 3/N~400 V, 50 Hz, rotor speed 2850 rpm, gray cast iron	20.732.0001
SR 200	for 230 V, 50 Hz, rotor speed 2850 rpm, gray cast iron	20.732.0003
Rotor Beater Mill SR 300, supplied with standard rotor, filter hose (240 mm), collecting receptacle (5 l) and base frame (Please order retaining frame and sieves separately)		
SR 300	for 3/N~400 V, 50 Hz, rotor speed 8100 rpm, stainless steel	20.733.1002
other electrical versions available on request		

Retaining frames and sieves for SR 200, SR 300		Item No.
Retaining frame for ring sieves 360°		
Retaining frame for ring sieves 360°, stainless steel		22.642.0001
Retaining frame for ring sieves 360°, chromium plated		22.642.0002
Ring sieves 360°, stainless steel	Trapezoid holes	Round holes
Aperture sizes in mm	0.08 0.12 0.20 0.25 0.50 0.75 1.00 1.25 1.50 2.00 3.00 4.00 10.00	
Item No.: 02.407...	... 0057 0026 0028 0029 0030 0031 0032 0058 0033 0034 0035 0036	0040
Retaining frame with grinding insert for sieves 180°		
Retaining frame with grinding insert for sieves 180°, stainless steel		02.143.0014
Sieves 180°, stainless steel	Trapezoid holes	Round holes
Aperture sizes in mm	0.08 0.12 0.20 0.25 0.50 0.75 1.00 1.25 1.50 2.00 3.00 4.00 10.00	
Item No.: 03.647...	... 0081 0039 0040 0041 0042 0043 0044 0045 0046 0047 0048 0049	0053

Rotors for SR 200, SR 300	Item No.	Item No.
	for SR 200	for SR 300
Distance rotor, stainless steel	22.717.0003	22.717.0004
Standard rotor, stainless steel	22.717.0001	22.717.0002

Accessories for SR 200, SR 300		Item No.
Base frame		
Base frame for SR 200		01.824.0028
Set of rollers for base frame		22.609.0003
Vibratory Feeders*		
Vibratory Feeder DR 100 for 220 -240 V, 50 Hz, complete with feeding kit, 75 mm feed chute, hopper and holder		70.937.0056
Vibratory Feeder DR 100 for 110 -120 V, 60 Hz, complete with feeding kit, 75 mm feed chute, hopper and holder		70.937.0057
Stand for using DR 100 with SR 200, SR 300		22.742.0003
Filter and collecting receptacles		
Ring-type filter with trapezoid hole sheet for 5 liter collecting receptacle		22.187.0001
Dust filter clamping rings for ring-type filter, with 5 dust filters		22.748.0001
Dust filter for ring-type filter, 25 pieces		22.524.0002
Stainless steel collecting receptacle, 5 liter		01.011.0023
Filter hose for 5 liter collecting receptacle, length 240 mm, with comfort flange		22.187.0003
Spare filter hose for 22.187.0003		02.186.0027
Plastic collecting receptacle, 30 liter, incl. filter hose and comfort flange		22.003.0011
*accessories for vibratory feeders: please refer to "Assisting" brochure		

# Applications

## Cross Beater Mill

The cross beater mill SK 100 is suitable for coarse and fine size reduction, either in batches or continuously. It processes medium-hard and brittle materials with a hardness of up to approx. 6 on Mohs' scale. Cross Beater Mills are typically used in the **construction industry and metallurgical plants** due to their **rugged design** and simple operation.

### Free test grinding

As part of RETSCH's professional customer support we offer our customers the individual advice required to find the optimum solution for their sample preparation task. To achieve this our application laboratories process and measure samples free-of-charge and provide a recommendation for the most suitable method and instrument.

For more information please visit our website [www.retsch.com/testgrinding](http://www.retsch.com/testgrinding).



The main areas of application for cross beater mills are:

#### Ceramics and glass

**Construction materials**  
cement clinker, gypsum, lime

**Geology and metallurgy**  
coal, coke, chamotte, granite, ores, slag

and many more...

### Application examples

Cross Beater Mill	Mill version	Bottom sieve aperture size	Feed size	Sample amount	Grinding time	Final fineness
Cement clinker	Hardened steel	4 mm	2-15 mm	500 g	3 min.	90% <1 mm
Coal	Gray cast iron	0.5 mm	1-15 mm	450 g	1 min.	95% <300 µm
Copper phosphor	Stainless steel	0.75 mm	1-3 mm	500 g	3 min.	90% <400 µm
Gravel	Stainless steel	0.5 mm	8 mm	1,000 g	5 min.	80% <2 mm
Lime	Stainless steel	0.75 mm	5-15 mm	170 g	5 min.	90% <250 µm
Magnesium carbonate	Stainless steel	2 mm	5-15 mm	400 g	3 min.	98% <1 mm
Refractories	Stainless steel	3 mm	0-3 mm	1,900 g	2 min.	90% <1 mm
Slag	Stainless steel	0.5 mm	1-15 mm	150 g	1 min.	98% <315 µm
Sodium chlorite	Stainless steel	2 mm	1-15 mm	850 g	2 min.	90% <1 mm
Tarmac	Stainless steel	3 mm	1-15 mm	1,500 g	2 min.	90% <1 mm

This chart serves only for orientation purposes.

RETSCHE's application database contains more than 1,000 application reports. Please visit [www.retsch.com/applicationdatabase](http://www.retsch.com/applicationdatabase).

# Cross Beater Mill

## SK 100



SK 100  
with  
base frame

**Robust and safe**

### Hard-to-beat size reduction

The RETSCH Cross Beater Mill SK 100 is intended for **universal use**: from sample preparation in laboratories and industrial plants, through pilot installations up to preparing sample batches in production facilities.

The maximum feed size for bulk goods is 15 mm, for single-piece feed 20 mm. The final fineness and throughput depend on the breaking behavior of the feed material and the aperture size of the bottom sieve. Due to the powerful drive it is possible to achieve a fineness  $<100 \mu\text{m}$  in a single working step in many cases.

### Convenient and safe operation

#### Benefits at a glance

- Suitable for batchwise operation of larger quantities
- Defined final fineness due to bottom sieves with aperture sizes from 0.12 - 10 mm
- Exchangeable grinding and sieve inserts
- Easy cleaning
- Quick-action door lock and motor brake

**The SK 100** offers the highest possible degree of **operating safety**. For example, if the off-switch is pressed or the door is opened, the motor brake ensures that the rotor will come to a standstill in less than 0.5 seconds. The feed hopper, like the optimized sample outlet, is equipped with an access barrier that also **prevents sample splash-back**. The SK 100 is easy to clean which helps to reduce preparation

time. The quick-action door lock allows rapid access to the grinding chamber and the high-quality sample outlet surface simplifies cleaning.

RETSCH cross beater mills are robust and maintenance-free and comply with the CE guidelines. Their high-quality finish also guarantees that the mills will have a long working life.

### SK 100 technology

Size reduction in cross beater mills takes place by hammering, impact and shearing effects. The feed material passes from the hopper directly into the center of the grinding chamber, where it is caught by the cross beater and ground between the baffle plates of the cross beater and the toothed grinding insert. As soon as the material is smaller than the

aperture size of the bottom sieve used, it passes through the sieve and enters the collecting receptacle. The air drawn in through the hopper by the cross beater accelerates the discharge of the ground material. The airborne fine fraction is separated off by a downstream filter system.



# Robust and efficient

## Bottom sieves

Bottom sieves made from trapezoid or round hole sheet are available in 14 aperture sizes. For heavy-metal-free grinding bottom sieves made from steel St 1203 are available in 6 aperture sizes.



## Accessories

The standard equipment supplied with the SK 100 includes a **5 l stainless steel collecting receptacle** and a textile filter hose. The **filter hose** is fixed between the mill and collecting receptacle and effects a discharge of the air flow produced by the rotating rotor. An accelerated material throughput and a gentle size reduction process are further advantages.

A **ring filter-type with stainless trapezoid hole sheet** (aperture size 63 µm) can be used with or without a

Performance data	SK 100
Application	size reduction
Field of application	agriculture, chemistry/plastics, construction materials, environment, geology/metallurgy, glass/ceramics
Feed material	medium-hard, brittle
Feed size*	<15 mm
Final fineness*	<100 µm
Collector volume	5 or 30 l
Technical data	
Drive	3-phase and 1-phase motors
Motor brake	yes
Drive performance	1.1 kW
Motor speed at 50 Hz (60 Hz)	2,850 rpm (3,420 rpm)
Rotor peripheral speed at 50 Hz (60 Hz)	22 m/s (26 m/s)
W x H x D (with base frame)	560 x 1,150 x 700 mm
Weight (with base frame)	approx. 57 kg
Noise values (noise measurement according to DIN 45635-31-01-KL3)	
Emission value with regard to workplace	L <sub>PAeq</sub> 86 dB(A)
Measuring conditions:	
Feed material	quartz gravel, grain size <3 mm
*depending on feed material and instrument configuration/settings	

dust filter unit instead of the textile tube; this is easier to clean, particularly with fine dusts, and ensures a higher stability for the collecting receptacle.

For larger sample amounts we recommend the use of the electromagnetic **Vibratory Feeder DR 100** for uniform material feed and the **30 l collector** with corresponding filter hose.

The SK 100 can be bench-mounted or installed on the optional base frame.



## Mill versions

The mill housing is made from cast aluminum. Depending on the application the grinding insert and grinding tools may be selected from various options. Because of its superior characteristics, **stainless steel** suits the vast majority of samples and is preferred for its ease-of-use. Grinding tools of **hardened steel** show the best resistance to abrasive materials while **gray cast iron** is considered as the inexpensive alternative. For grinding without heavy metals, a combination of **cast iron and steel 1.1740** is available. Details are shown in the table.

Versions	Grinding insert	Cross beater	Baffle plates
SK 100, cast iron	cast iron	cast iron	hardened steel
SK 100, hardened steel	hardened steel	cast iron	hardened steel
SK 100, stainless steel	stainless steel	stainless steel	stainless steel
SK 100, heavy-metal-free	cast iron	cast iron	steel 1.1740

## Order data for Cross Beater Mill SK 100

Cross Beater Mill SK 100						Item No.
Supplied with grinding insert, cross beater, baffle plates, filter hose (240 mm) and collecting receptacle (5 l) (Please order base frame and bottom sieve separately)						
	version:	cast iron	hardened steel	stainless steel	heavy-metal-free	
SK 100	for 3/N~400 V, 50 Hz	20.735.0001	20.735.0002	20.735.0003		20.735.1001
SK 100	for 230 V, 50 Hz	20.735.0007	20.735.0008	20.735.0009		20.735.1007
SK 100	for 110 V, 60 Hz	20.735.0010	20.735.0011	20.735.0012		20.735.1010

Bottom sieves for SK 100													Item No.		
Bottom sieves	Trapezoid holes							Round holes							
Aperture sizes in mm	0.12	0.20	0.25	0.50	0.75	1.00	1.50	2.00	3.00	4.00	5.00	6.00	8.00	10.00	
Bottom sieves, stainless steel															
Item No.: 02.407...	... 0059	0013	0001	0002	0003	0004	0005	0006	0007	0008	0009	0010	0011	0012	
Bottom sieves, steel St 1203 for heavy-metal-free grinding															
Item No.: 02.407...	... 0083	0084	0085	0086	-	0087	-	0088	-	-	-	-	-	-	-

Grinding tools for SK 100					Item No.
	cast iron	hardened steel	stainless steel	steel 1.1740	
Grinding inserts	22.443.0001	22.443.0002	22.443.0003	-	
Cross beater	22.716.0001	-	22.716.0002	-	
Baffle plates (3 pieces)	-	22.526.0001	22.526.0002	22.526.0006	

Accessories for SK 100		Item No.
Base frame		
Base frame for SK 100		01.824.0028
Set of rollers for base frame		22.609.0003
Vibratory Feeders*		
Vibratory Feeder DR 100 for 220 -240 V, 50 Hz, complete with feeding kit, 75 mm feed chute, hopper and holder		70.937.0056
Vibratory Feeder DR 100 for 110 -120 V, 60 Hz, complete with feeding kit, 75 mm feed chute, hopper and holder		70.937.0057
Stand for using DR 100 with SK 100		22.742.0003
Filter and collecting receptacles		
Ring-type filter with trapezoid hole sheet for 5 liter collecting receptacle		22.187.0001
Dust filter clamping rings for ring-type filter, with 5 dust filters		22.748.0001
Dust filter for ring-type filter, 25 pieces		22.524.0002
Stainless steel collecting receptacle, 5 liter		01.011.0023
Filter hose for 5 liter collecting receptacle, length 240 mm, with comfort flange		22.187.0003
Spare filter hose for 22.187.0003		02.186.0027
Plastic collecting receptacle, 30 liter, incl. filter hose and comfort flange		22.003.0011
*accessories for vibratory feeders: please refer to "Assisting" brochure		

# Retsch®

**Retsch GmbH**  
Rheinische Straße 36  
42781 Haan, Germany

Telephone +49 21 29/55 61-0  
Telefax +49 21 29/87 02  
E-Mail info@retschi.com  
Internet www.retschi.com

a VERDER company

RETSCH – Your specialist for sample preparation offers you a comprehensive range of equipment. Please request information on our crushers, mills, sieve shakers, sample dividers, feeders as well as cleaning and drying machines.